


# ICONS.



**01** Accentuates the freshness of fruit and vegetables. **02** Warm yellowish light gives a perfect appearance to cheese and other dairy products. **03** Fresh and cooked meats have a saturated red color under this light. A boost of red for the meat counter. **04** Bluish white light promotes freshness of fish and seafood. **05** This light color has a light brown tinge to give an oven-fresh appearance to crusty bakery products. **06** Optimized light spectrum for perfect fashion presentation. **07** The average value of the Art series is an impressive CRI 98. MacAdam 2 ellipses are used in this special product category, to provide an outstanding colour consistency. **08** Spectral LED matches natural light over the visible spectrum. **09** Infinity LED: Human-centric lighting allows autonomic control of CCT. With a high CRI >90 and a tight initial colour tolerance of 1 step MacAdam. Create a wide range of colours (through the combinations of different LED's) for spectacular lighting scenes or mood illumination. **10** For spot and accent lighting in fashion, retail, hospitality and supermarket applications. **11** Wireless lighting control based on Bluetooth. **12** Dim to a warmer colour from 3000K to 1800K for creating the right atmosphere. **13** Light colour from 2700K to 6500K to set an individual colour temperature. Used for wellbeing (daylight simulation) and for increasing the performance in offices and workshops. **14** Phase-cut dimming. **15** Digital dimming interface. **16** Analog dimming interface. **17** The clear glass is protecting the light source and reflector from dust and other dirt that could enter the optical part of the luminaire. **18** Frosted glass protects the light source and reflector from dust and dirt. It also widens the beam and creates a different footprint. **19** Honeycombs are widely used to reduce the direct glare. Luminaires with honeycombs have usually a tighter beam. **20** Shape the light by using barndoors. Two side flaps closed together produce a slim light shape, all four doors closed together will produce a square focussed beam of light. **21** Built-in emergency unit for escape route lighting. **22** Unified Glare Rating < 19, suitable for reading, writing, training, meetings and PC based working environments. **23** Ingress Protection 40: protected against solid objects, not watertight from optical side. **24** Ingress Protection 65: dustproof and protected from water spray from optical side. **25** Type of power distribution specially developed for the connection of lighting cables above the ceiling. **26** Also suitable for 1-phase track. **27** Replaceable (LED only) light source by a professional. **28** Replaceable control gear by a professional.